

PRINT COATING SUPPLY SYSTEM
FOR
PLURALITY OF COATING SUBSTANCES

The present application claims the benefit of U.S.

5 Provisional Patent Application Serial No. 60/222,704 filed August
2, 2000, and which is incorporated by reference herein.

Background

Field of the Invention

10 The present invention relates to a printing coating system for
the printing industry and, more particularly, to a coating material
supply system and a method for supplying print coatings.

Description of Related Art

15 In the printing industry, and in particular, when printing or
coating web, sheet or discrete products("printed product"), a
coating material is used and a drum is partially submersed in a
tray filled with the coating material. The coating drum rotates in
the coating material and the coating material is deposited from a
surface of the coating drum to the printed product passing there-
over in the press (printing press). Subsystems are designed and
20 incorporated to perform such functions as level detectors for
coating material as well as a plurality of other aspects of the

coating operation. A more complete discussion of such systems and, particularly, a printed product coating material supply apparatus and method are set forth and shown in co-pending U.S. Patent Application Serial No. 09/422,845 ^{1734 118/694} which is incorporated herein by reference.

A problem in prior art coating systems is that when a type of coating substance was to be changed to another type of coating substance in a printing or coating system, the entire printing/coating system had to be stopped, partially dismantled, manually cleaned, and then restarted again. Precious time was utilized during the cleaning process that delayed printing or coating the product.

For example, an aqueous coating may be used in a particular printing/coating press or certain printed product production runs. Other printed product production runs may require a liquid ultra-violet light-sensitive coating ("UV coating").

Conventional UV coatings are not compatible with aqueous coatings. When the UV coating material contacts with aqueous coating material, a gummy substance may form, which has an adverse effect on the printing/coating press. Thus, after using an aqueous coating in a press, the aqueous coating residue remaining in the coating system's circulation lines must be

removed from the circulation lines prior to introduction of a UV coating material. The aqueous coating residue is generally removed by dismantling the supply lines and flushing the supply lines manually with appropriate chemicals or compressed air.

5 After the aqueous coating residue is manually removed from the system's circulation lines, the system is reassembled. UV coating can now be introduced to the system and be utilized in the printing/coating press without creation of a gummy residue. Furthermore, metallic inks and other modern inks and coating substances have reaction and compatibility issues when used in
10 the same press. In essence, the incompatibility of various inks and coating substances create significant maintenance and efficiency issues in the printing industry.

To better clarify the maintenance issues, all supply lines
15 as well as reservoirs, nozzles, valves, etc. which are in contact with coating materials must be purged and cleaned manually of all coating residue before a new coating material is introduced thereinto. If reservoirs and/or circulation lines are difficult to access and/or clean, then the cost of the maintenance is
20 significantly increased. Further, the downtime for the maintenance can itself become a prohibitive factor with regard to a particular coating system design and/or the feasibility for the

use of a particular coating type in a multiple coating application system. It would be an advantage to provide a single coating system that allows for a plurality of coating substances to discretely flow therethrough. The discrete flow would minimize the amount of manual maintenance and cleaning between coating changes and minimize the costs and time required to change a coating material within the system. It would likewise to be an advantage to provide such a system that is highly reliable and energy efficient.

Summary of Invention

The present invention relates to a printing supply system for a plurality of coating substances and a method for supplying the plurality of coating substances. In particular, the printing supply system includes a first supply line for supplying a first fluid and a second supply line for supplying a second fluid. A first valve member is connected to the first supply line and to the second supply line. A supply tube is provided connected to the first valve member for providing a selected fluid to a press, the selected fluid being one of either the first fluid or the second fluid.

A drain tube is provided for extracting the selected fluid from the press. A second valve member is connected to the drain tube. A first return line and a second return line are connected to the second valve member.

5 A conduit is provided between the supply tube and the drain tube, for enabling draining of the supply tube and the drain tube between selection of the first fluid and the second fluid.

10 In certain preferred embodiments, a programmable logic controller is provided to direct overall operation of the system. The connecting conduit may have a first conduit valve substantially near the supply tube and a second conduit valve substantially near the drain tube. Both first and second conduit valves are electrically connected to the programmable logic controller.

15 A pump and valve portion is provided in the system for moving fluids and/or gases therethrough. A cleaning fluid or water drum adapted to contain cleaning fluid or water is connected to the pump and valve portion. The pump and valve portion in combination with the water drum is adapted to
20 circulate the water through the printing supply system for cleaning the system.

In operation, the first fluid is supplied to and from the press via the supply tube and the drain tube respectively, with the conduit valve or valves in a closed position. The first fluid supply is then stopped and drained from the press via the drain tube. The supply is next switched to a cleaning fluid. The conduit valve or valves are adjusted to an open position which allows fluid flow therethrough. The cleaning fluid is then supplied through the supply tube, the drain tube and the conduit.

After sufficient time for cleaning, the cleaning fluid supply is halted and drained from the supply tube, the drain tube and the conduit. Another switching step occurs from the cleaning fluid to the second fluid. The conduit valve or valves are then placed in a closed position to prevent fluid flow therethrough. Finally, the second fluid is supplied to and from the press via the supply tube and the drain tube.

Brief Description of the Drawings

Features, aspects, and advantages of the present invention will become better understood with regard to the following description, appended claims, and accompanying drawings where:

FIGURE 1 is a diagrammatic schematic of an exemplary coating supply system for a plurality of coating substances in accordance with the principles of the present invention;

FIGURE 2 is a perspective view of a supply drum with supply and return lines connected thereto and a fluid level sensor;

FIGURE 3 is an enlarged cross-sectional view of the supply drum of FIG. 2; and

FIGURE 4 is a diagrammatic schematic of an exemplary water supply and heating system for use with the coating supply system of FIG. 1.

Detailed Description of the Preferred Exemplary Embodiments

Referring first to FIG. 1, there is shown a diagrammatic schematic illustration of one embodiment of a print coating supply system 10 for different coating substances in accordance with the principles of the present invention. The supply system 10 includes a programmable logic controller 20 ("PLC") within a cabinet 30 ("PLC cabinet"). It is to be understood throughout this application that the PLC cabinet 30 includes certain elements of the supply system 10, including but not limited to air pumps, actuators, actuator valves, fluid pumps, a programmable logic circuit such as a micro-controller, and the

like. It is also to be understood that the printing press generally encompasses the section designed by reference "A". The PLC cabinet 30 is connected to a plurality of supply lines and return lines 40 extending from a lower region 50 of the PLC cabinet 30. The PLC cabinet 30 is also connected to a plurality of electrical lines 60 extending from the PLC cabinet 30. The reference to the supply lines and return lines 40 and electrical lines 60 extending from upper and lower ends of the PLC cabinet 30 is only for purposes of discussion and clarity of the Figure and in no way limits the present invention. Neither the size of the supply lines and return lines 40 nor the relative size of the PLC cabinet 30 are to be considered any more than diagrammatical schematic references.

Referring still to FIG. 1, the supply lines and return lines 40 are shown assembled beneath a coating tray 80. It is understood that the coating tray may be replaced by a chamber device or other device used to provide coating materials or ink to a printed product. The supply and return lines 40 are of a type typically used in a printing system. The coating tray 80 is supplied with a coating material 90 through a supply tube 100. The coating material 90 is drained from the coating tray 80 by a drain tube 110. The supply tube 100 is connected to a first

coating supply line 140 and a second coating supply line 150.

The first coating supply line 140 has an in-line check valve 115 oriented to allow flow of coating material 90 to supply tube 100 and prevent back-flow therefrom. The first coating supply line

5 140 also has a first solenoid supply valve 120 actuatable to control flow of coating material 90 through the first supply line 140 into the supply tube 100. Second coating supply line 150 has

10 a second solenoid supply valve 125 actuatable to control flow of coating material 90 through the second supply line 150 into the

supply tube 100. A first coating return line 160 has a first solenoid return valve 130 for controlling flow of coating

material 90 from coating tray 80 to the return line 160. A

second coating return line 170 has a second solenoid return valve 135 for controlling flow of coating material 90 from coating tray

15 80 to the return line 170. A solenoid main return valve 180 is provided in drain tube 110 to control flow from the coating tray

80 to the return lines 160, 170. A solenoid conduit valve 190 resides in a connecting conduit 200, which connects and extends

between the supply tube 100 and drain tube 110. The operation of

20 the conduit valve 190 in connection herewith is described in more detail below.

Referring still to FIG. 1, there is shown a first supply drum 210 containing a first coating and a second supply drum 220 containing a second coating. Supply drums 210, 220 are connected to the PLC cabinet 30 by the supply and return lines 40 extending from the supply drums 210, 220 to the lower region 50 of the PLC cabinet 30. The supply drums 210, 220 are preferably constructed or fitted with non-contact coating level sensors 230, 240. The non-contact coating level sensors 230, 240 are preferably secured in the upper regions of supply drums 210, 220, respectfully. The non-contact coating level sensors 230, 240 provide information to the PLC 20 within the PLC cabinet 30 by virtue of a first communication line 250 extending from sensor 230 and a second communication line 260 extending from the sensor 240. In this way the PLC 20 within the PLC cabinet 30 is able to determine the level of the respective coatings within the supply drums 210, 220 for actuation and control of the a supply pump system 225 and a return pump system 235, preferably located within the PLC cabinet 30) for introduction of the coating material 90 into the supply lines and return lines 40 discussed above. It is to be understood that the supply pump system 225 and return pump system 235 may have multiple connections to the various supply lines and return lines 40 as the application requires, and that one of

ordinary skill in the art could easily devise such connections.

For example, commonly owned and co-pending U.S. Patent Application Serial No. 09/422,845 which is hereby incorporated by reference discloses an exemplary pumping system.

5 Each solenoid valve 120, 125, 130, 135, 180, and 190 is in communication with the PLC 20 of the PLC cabinet 30 via an electrical line 60. In this manner, the flow of coating fluid can be monitored and controlled by the PLC 20. For example, a first coating material from the first supply drum 210 can be
10 supplied via a supply line 270 while the first supply valve 120 is open, the second supply valve 125 is closed, the first return valve 130 is open, and the second return valve 135 is closed. The first coating material may then return via the return line 280 to the first supply drum 210. Accordingly, when the first
15 supply valve 120 is closed, the second supply valve 125 is open, the first return valve 130 is closed, and second return valve 135 is open, a second coating material from the second supply drum 220 can be supplied in the same manner by a supply line 290 and returned to the second supply drum 220 by a return line 300.

20 Referring now to FIGS. 1 and 4 in combination, also situated inside the PLC cabinet 30 is a cleaning fluid or water drum 310 containing cleaning fluid or water 320. The water 320 within the

water drum 310 is maintained at an elevated temperature during operation of the supply system 10 via a heating element 330.

Level sensors 340 are provided in the water drum 310 and are in electrical contact with the PLC 20 via electrical lines 60 for

5 determination of the amount of water in the water drum 310. The water can be circulated from the PLC cabinet 30 to the coating tray 80 in the same manner as the coating material 90. A water

source 318 having a source pump (not specifically shown)

electrically connected to the PLC 20 via an electrical line 60 is

10 provided for supplying water 320 to the water drum 310 via a

water source line 324. A water valve 314 is connected in-line

with the water source line 324 and has an electrical line 60

connected to the PLC 20 for regulating water flow. A water

system supply line 326 is connected to the water drum 310 for

15 supplying water 320 to the system 10 via the supply and return

lines 40. A plurality of water valves 314 connected to the PLC

20 via electrical lines 60 are connected in-line to the water

system supply line 326 for regulating water flow. A manual drain

316 is provided along the water system supply line 326 to allow a

user to manually drain the water 320 from the water drum 310. In

an optional configuration, a spray bar supply line 328 having a

water pump 312 and a water valve 314 is provided for supplying

water 320 to a spray bar 322. The water valve 314 and water pump 312 are both connected to the PLC 20 via electrical lines 60. A more complete discussion of the flow of the coating material and 90 and water 320 is described hereunder.

5 Referring back to FIG. 1, the conduit valve 190 is positioned adjacent to the drain tube 110 and supply tube 100 for cleaning the coating circulation and supply system 10 prior to changing to a different coating material. The conduit valve 190 is connected to the PLC 20 via respective communication wires
10 360.

Upon completion of running a first coating material (such as an aqueous based fluid) within the coating tray 80 through the supply system 10, a supply pump system 225 is turned off while a return pump system 235 continues to pump fluid out of the coating
15 tray 80 via the drain tube 110 and return line 160 or 170. A residue from the coating material 90 may remain in the supply tube 100, coating tray 80 and drain tube 110. The residue may be manually cleaned from the inside surfaces of the coating tray 80 after the first coating is drained through the drain tube 110.

20 Excess coating material 90 in the form of droplets or residue remaining inside the supply tube 100 must be removed. A low pressure vacuum (preferably created by the return pump within

the PLC cabinet 30) originating from the PLC cabinet 30 is utilized to draw air or water 320 (from the water drum 310) through the connecting conduit 200 between the drain tube 110 and supply tube 100.

5 Referring now to FIG. 2, there is shown a prospective view of a coating material container such as the first supply drum 210 with a non-contact coating level sensor 230 disposed on top thereof. Supply lines 270 and return lines 280 are shown connected to the first supply drum 210 via a mounting bung 370 to provide access to the coating material contained therein. The supply line 270 and return line 280 may be inserted into the first supply drum 210 and mounting bung 370 by the use of collars 380 or other tubing connectors. It is conventional in the print industry to store coating material in a drum style container. In many circumstances, the drum style container is used as the source of coating material for a printing or coating system. In some printing and coating systems, it is advantageous to circulate the flow of coating out of the drum, through the system and back to the drum during the operation of an exemplary printing coating system. It is for this reason that the level of coating within a supply drum must be carefully maintained in

order to prevent an overflow of coating material or the sucking of air from an empty drum during the printing operation.

Referring now to FIG. 3, there is shown a cross-section of the first supply drum 210 to illustrate the non-contact nature of the first non-contact coating level sensor 230, and an exemplary return line 390 construction. During operation of the print coating supply system 10, it is common for air to accumulate and integrate with the coating material 90 as it flows to and from the first supply drum 210. To alleviate build-up of foam and other undesirable properties in the coating material due to the presence of the air, two or more slots 400 are provided along the exemplary return line 390 in the first supply drum 210 to dissipate and minimize the effects of any such air that may be collected in the exemplary return line 390 and in the first supply drum 210 during operation.

During initial, transient and steady-state flow of the print coating supply system 10, fluid is removed from the first supply drum 210 and flows through the supply system 10 after a predetermined signal is sent from the PLC 20 in the PLC cabinet 30. A first non-contact coating level sensor 230 is in communication with the PLC 20 within the PLC cabinet 30 via an electrical line 60 extending from the first non-contact coating

level sensor 230 and terminating at the PLC cabinet 30. Should the fluid level in the first supply drum 210 become too low during operation, the PLC 20 is alerted by the first non-contact coating level sensor 230. Thereafter, the PLC 20, which may be programmed accordingly, indicates the need for a new supply drum to be attached to the print coating supply system 10, or to indicate the need to increase return flow from the coating tray 80. A non-contact level sensor 230 may be provided on the coating tray 80 to aid the determination of whether the fluid contained therein reaches a high or low level. The non-contact level sensor 230 communicates this information to the PLC 20. In an exemplary case, coating fluid may be removed from the supply drum 210 faster than it is being returned from the coating tray 80. In this case, the non-contact level sensor 230 will indicate a defect in the flow operation and/or pumping operation to the PLC in the form of a low fluid level signal.

While several types of level sensors may be successfully substituted for a non-contact level sensor, the use of a non-contact level sensor is preferred. Coating materials tend to be viscous and leave an undesirable coating on contacted elements. Therefore, to prolong the life and reliability of sensor components, it is desirable to use a non-contact sensor. A

preferred non-contact level sensor utilizes changes in atmospheric pressure to determine the fluid level in the first supply drum 210 or second supply drum 220. Other types of non-contact level sensors can include sensors that utilize ultrasonic sound, electro-magnetic waves, or other acoustic waves to determine the fluid level.

It has been postulated that heating certain UV fluids enhances the properties of the UV fluid during operation of the print coating supply system 10. Therefore, in an alternate embodiment also shown in FIG. 4, supply lines 40 containing fluid from the UV drum are allowed to thermally communicate with the heated water within the water drum 310 prior to the UV fluid being directed toward the press. The resulting heat transfer from the water to the UV fluid should, therefore, enhance the properties of the UV fluid as is believed in the art.

Referring to Figures 1-4 in combination, during operation of the print coating supply system 10, a first fluid travels from the first supply drum 210 through the supply line 270 and into the PLC cabinet 30. The first fluid is next pumped out of the PLC cabinet 30 via supply pump system 225 through the first coating supply line 140 and to supply tube 100. The fluid may be heated in a manner described above by allowing the fluid to

thermally communicate with the heated water drum 310 within the PLC cabinet 30. Next, the fluid is pumped into the supply tube 100 and into the coating tray 80. The unused coating material continues its circulation route through the drain tube 110 and subsequently through the first drain line 160. The fluid next travels back into the return line 280, finally completing one circulation cycle at the first supply drum 210.

To switch from a first fluid (e.g. aqueous based fluid) to a second fluid (e.g. UV fluid), the PLC 20 shuts off its supply pump system 225, which causes all supply flow to cease. The return pump system 235, remains on to remove remaining fluid in the coating tray 80, drain tube 110, second return valve 130, and return line 160. The PLC 20 then switches the supply line to the water drum 310, where heated water (from the water drum 310) is pumped from and allowed to circulate through the supply lines 140, 150, supply tube 100, coating tray 80, drain tube 110, and return lines 160, 170. After the water has finished circulating and has been returned to the PLC cabinet 30 and into the water drum 310 or sent to a waste container (not shown), return pump system 235 remains on and draws air into the drain tube 110 and the supply tube 100 after the opening and configuring of the second conduit valve 190. Once the air flow has been

substantially removed and fluid droplets remaining have evaporated after the water/air flush, the return pump system 235 is turned off, the conduit valve 190 is closed to prevent incoming flow from the supply tube 100 and drain tube 110. The first supply valve 120 is closed, the second supply valve 125 opened, the first return valve 130 is closed, and second return valve 135 is opened to allow the second fluid to begin circulation from the second supply drum 220 via the supply pump system 225 with little risk of contamination from the first fluid.

It is understood that various pumping configurations can be provided within the PLC cabinet 30 that can accommodate the requirements of the present invention. One of ordinary skill in the art could easily create at least one pumping configuration that will accomplish the requirements of the present invention and as such, a specific pumping configuration is not specifically shown in the present Figures.

It is believed that the operation and construction of the present invention will be apparent from the foregoing description of the preferred exemplary embodiments. While the print coating supply system for a plurality of coating substances shown is described as being preferred, it will be obvious to a person of

ordinary skill in the art that various changes and modifications made may be made therein without departing from the spirit and the scope of the invention.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2